

ELECTRICAL HOT WATER H.P. CLEANERS &gt; IDROPULTRICI ELETTRICHE AD ACQUA CALDA



# VENTO



## 135 - 150



### GENERAL FEATURES

- Comet electrical pump with three axial pistons arranged horizontally with pump at the bottom and an all-metal construction without any plastic used for the structural components and brass pump head
- Pressure gauge
- Built-in fuel and detergent tanks
- Direct low-pressure suction of water with detergent
- **EASY-START** device
- **TotalStop** device
- Delayed burner start
- Safety valve
- Amperometric motor protection
- **Temperature setting thermostat**



### CARATTERISTICHE GENERALI

- **Elettropompa Comet a tre pistoni assiali disposta in orizzontale con pompa in basso e costruzione interamente in metallo, senza materiale plastico nei componenti strutturali e testata in ottone**
- Manometro pressione
- Serbatoio gasolio e detergente integrati
- Aspirazione acqua diretta con detergente in bassa pressione
- Dispositivo **EASY-START**
- Dispositivo **TotalStop**
- Partenza ritardata del bruciatore
- Valvola di sicurezza
- Protezione amperometrica del motore
- **Termostato di regolazione temperatura**
- Uso semiprofessionale

- Big rubber wheels
- Ruote di grandi dimensioni

- Practical lance and gun storage
- Pratico alloggiamento della pistola e della lancia

Hose reel with 10 m high-pressure hose  
(for EXTRA models only)  
Avvolgitubo con tubo alta pressione in gomma 10 m.  
(solo per modelli EXTRA)



CODE CODICE	MODELS MODELLI	Electrical			Pressure		Flow	Power	Temp	Capacity	Weight	Dimensions		
		Ph	V	Hz	bar	MPa							(L x W x H) cm	
9044 1001	VENTO CLASSIC 150	1	230	50	150	15,0	540	2,7	90	15	3,11	4,5	85	89 x 50 x 82
9044 1003	VENTO CLASSIC 135	1	230	50	135	13,5	600	2,7	90	15	3,11	4,5	85	89 x 50 x 82
9044 1002	VENTO EXTRA 150	1	230	50	150	15,0	540	2,7	90	15	3,11	4,5	85	89 x 50 x 82
9044 1004	VENTO EXTRA 135	1	230	50	135	13,5	600	2,7	90	15	3,11	4,5	85	89 x 50 x 82

**STANDARD ACCESSORIES > DOTAZIONE STANDARD**

CLASSIC	EXTRA
	Gun GC 251 with protection <i>Pistola GC 251 con protezione</i>
	Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>
	Fan shape nozzle 15°, 1/4" MEG connection <i>Ugello con getto a lama 15° attacco 1/4" MEG</i>
	SAE 100, 8 m rubber delivery hose kit <i>Kit tubo gomma mandata SAE 100 - 8 m</i>
	SAE 100, 10 m rubber delivery hose kit <i>Kit tubo gomma mandata SAE 100 - 10 m</i>